

Technical Data Sheet



**CLEARMATE
SUPERIOR TILE STAIN
REMOVER**

JKTYLO™

PREMIUM ADHESIVES & GROUTS

Clearmate

SUPERIOR TILE STAIN REMOVER

Technical Data Sheet



JKTylo Clearmate is a ready to use, super-active tile cleaner for regular and constructional stains on all types of tiles. It maintains the shine of tiles and grouts and is applicable on interiors and exteriors, wall and floor surfaces.

Key Benefits and Features

- Removes difficult stains easily
- Easy to use
- Cleans all types of tiles
- For interiors & exteriors

Substrates

- Ceramic tiles
- Vitrified tiles
- Porcelain tiles
- Glazed & unglazed tiles
- Glass mosaic tiles

Application Method

1. For mild blemish spots/ layers, mix JKTylo Clearmate with water in 1:1 proportion.
2. Soak the cloth or sponge in the diluted solution and rub the surface till the spots/ layers are removed.
3. For stubborn spots/ layers, neat JKCement JKTylo Clearmate (without mixing with water) shall be used for cleaning. Recommended to test in a small area before cleaning the complete area.
4. For routine tile cleaning, dilute 2 capful JKTylo Clearmate with half bucket water and use diluted solution for cleaning the tiles.

Technical Information

Physical State	Liquid
Color	Clear liquid
Specific Gravity	at 270 °C : 1.002 ± 0.001
Viscosity	at 270 °C : more than water
Soaking Time	5 minutes after application
Dilution	For normal cleaning - 100 mL in 3 L water For cleaning of spotted surface – use undiluted
Coverage	4-6 m ² / L (Varies on the condition of surface)

Packing : Bottle 1 L and 500 mL

Storage : Store in dry and covered area

Precautions During Usage:

- Keep away from wood, metal and other acid sensitive materials.
- Excess usage may etch, lighten or alter the color of tiles and grouts.
- Recommended to wear hand gloves and eye glasses during application of tile cleaner.
- Do not use on marble and similar stones.

Disclaimer :

The company provides guarantee against defective material, but the application and usage of products are made without guarantee since the application conditions are not in its control. All products are tested under the recommended conditions of temperature $27 \pm 2^{\circ}\text{C}$ and humidity $65 \pm 5\%$. Company recommends to verify the suitability of product for intended use with the latest version of data sheet. The company may modify product data sheet without any prior notice. All technical characteristics are listed for guidance only and JKTylo technical team may be contacted for more information.



Registered Office : Kamla Tower, Kanpur - 208001

Ph. : 0512-2371478-85, Fax : 0512-2399854 E-mail : admin@jkcement.com

Corporate Office : Prism Tower, 5th Floor, Ninaniya Estate, Gwal Pahari,
Gurugram - 122102, Haryana Tel : +(91)124-6919000

Website : www.jkcement.com **Toll Free No. :** 1800 102 8868

Customer Care : customercare.white@jkcement.com

